



Rely on us.™

dayGraphica® 8894 Newsprinter

Gain confidence with reliability

Printing Blankets: Offset - No-Pack

You can count on the dayGraphica® 8894 for the cleanest and most precise ink transfer available for newsprint stock. Plus, you'll experience greater value and increased productivity with fewer blanket changes. Improve your profitability with confidence. Try the dayGraphica® 8894 for a confident day in the pressroom.

Advantages of dayGraphica® 8894 Newsprinter

- Designed to allow flexibility in packing requirements
- Can be run as a No-pack on Goss Headliner Offset
- Maximum smash resistance
- Rebounds quickly
- High density carcass prevents gauge loss and provides long life

HEATSET. DIRECTORY.
NEWS. SINGLE WIDE. DOUBLE WIDE.



FlintGroup

dayGraphica® 8894 Newsprinter

Gain confidence with reliability

Features	Benefits
Highly ground and buffed surface	Uniform gauge and consistency. Ideal texture for carrying and transferring ink. Maximum release characteristics. Precise printability.
Compatible rubber surface compound	Solvent resistant. Excellent abrasion resistance. Excellent release characteristics. More consistent feed characteristics.
Durability-engineered carcass	High-density carcass prevents gauge loss and provides long life.
Patented closed-cell compressible layer	Enables blanket to achieve precise and even printing pressure across entire printing surface. Maximum smash resistance. Key factor in blanket durability. Rebounds quickly.
Standard 4-ply gauge	Designed to allow flexibility in packing requirements. Can be run as a No-pack on Goss Headliner Offset.

Specifications:

Color: Green

Surface: Ground

Thickness:

1,93mm/0.076" ($\pm .0005$ ")

1,96mm/0.077" ($\pm .0005$ ")

Face Compound:

Solvent Resistant Rubber Blend

Hardness:

78° Shore A

Compressibility Deflection:

.006" Typical at 145 psi

.008" Typical at 290 psi

Elongation:

1.0% Typical at 57 ppi

Tensile Strength:

1640 ppi Typical

Inks,
blankets,
chemicals
& more

Rely on us™
to bring greater value to your pressroom.

For more information:

Flint Group
Print Media North America
14909 N. Beck Road
Plymouth, MI 48170
+1 734 781 4600
printmedia.na@flintgrp.com

www.flintgrp.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. Customers are responsible for confirming suitability of this product for their application. In no event shall Flint Group be liable for any errors, facts or opinions contained herein, or any claims by any party alleging reliance on these materials, regardless of the form of action.

Product names followed by a ® are trademarks registered by a Flint Group company.

Version 5/2015 Page 2 of 2