

*Rely on us.*SM



K+E Novacoat® oil-based overprint varnishes for sheetfed offset

Range overview

K+E® Novacoat® oil-based overprint varnishes – varied and variable

- x Varnishes have become increasingly important in recent years – not just as an aid to sophisticated design, creating gloss and matt effects or for spot coating, but first and foremost for protecting the printed product.
- x Flint Group oil-based varnishes are easily identified by the Novacoat® product name. Our portfolio is as diverse and variable as your daily printing challenges.
- x We offer a broad range of gloss, silk-matt and matt varnishes specially designed to cater for a variety of needs and broad area of applications in sheetfed offset printing.
- x Our oil-based varnishes provide ideal properties for almost all demands: from fast drying varnishes, to varnishes for optimum rub protection or very low yellowing characteristics, up to BIO-based versions for the use in perfecting presses or varnishes for the production of printed products that bear one of the European Ecolabels.
- x The property profiles within the range are so finely tuned with each other, that we can always offer you a suitable product for your individual requirements.
- x The following pages provide an overview of all products within our oil-based varnishes range. More detailed information on each varnish is available in the individual product literature.
- x Please contact us if you have questions about our Novacoat® oil-based varnishes – we'll be happy to help you!



FlintGroup

Novacoat® oil-based overprint varnishes





Product features	Printing properties							
	Gloss	Matt effect	Wet on Wet suitability	Wet on Dry suitability	Setting	Rub protection	Suitability for Perfecting	
Novacoat® oil-based overprint varnishes – high gloss varnishes								
Novacoat® 256 high gloss varnish	High gloss varnish with the fastest drying speed.	6	-	7	7	6	6	2
Novacoat® 4050 high gloss varnish	High gloss varnish for the highest gloss effect.	7	-	7	6	6	6	2
Novacoat® 4820 high gloss varnish	High gloss varnish for the best rub protection in straight-line printing.	6	-	6	6	6	7	2
Novacoat® 8844 high gloss varnish	High gloss varnish based on BIO-binders for perfecting.	6	-	7	5	5	7	7
Novacoat® 9911 high gloss varnish	High gloss varnish with very low yellowing characteristics.	6	-	6	6	6	7	4
1 = Characteristic weakly expressed 7 = Characteristic strongly expressed <i>The assessment of the varnish properties was made under standardised printing conditions. In individual cases, under special conditions, as in printing with very thick layers of varnish, the classification of certain properties may be different.</i>								

Don't use oil-based overprint varnishes on food packaging without functional barrier.

Please refer to the individual product literature for more detailed information of the Novacoat® oil-based varnishes.

You are welcome to contact us for further information.

Flint Group
Packaging & Narrow Web
 Sieglestrasse 25
 70469 Stuttgart, Germany

T +49 711 98 16-0
F +49 711 98 16-700
sheetfed@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH).

Novacoat® oil-based overprint varnishes



Product features	Printing properties						
	Gloss	Matt effect	Wet on Wet suitability	Wet on Dry suitability	Setting	Rub protection	Suitability for Perfecting
ishes – silk matt varnishes							
Silk matt varnish based on BIO-binders for perfecting.	-	3	7	5	5	6	6
Silk matt overprint sealer for excellent rub protection.	-	3	7	5	6	7	4
Silk matt varnish with very low yellowing characteristics.	-	3	7	6	6	6	5
1 = Characteristic weakly expressed 7 = Characteristic strongly expressed							
<i>The assessment of the varnish properties was made under standardised printing conditions. In individual cases, under special conditions, as in printing with very thick layers of varnish, the classification of certain properties may be different.</i>							

Don't use oil-based overprint varnishes on food packaging without functional barrier.

Please refer to the individual product literature for more detailed information of the Novacoat® oil-based varnishes.

You are welcome to contact us for further information.

Flint Group
Packaging & Narrow Web
 Sieglestrasse 25
 70469 Stuttgart, Germany

T +49 711 98 16-0
F +49 711 98 16-700
sheetfed@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH).

Novacoat® oil-based overprint varnishes



Product features	Printing properties						
	Gloss	Matt effect	Wet on Wet suitability	Wet on Dry suitability	Setting	Rub protection	Suitability for Perfecting
ishes – matt varnishes							
Matt varnish for the best matt effect.	-	7	7	6	7	6	2
Matt varnish for the best rub protection in straight-line printing.	-	6	7	6	6	7	2
Matt varnish based on BIO-binders for perfecting.	-	6	7	5	5	6	6
Matt varnish with very low yellowing characteristics.	-	6	7	6	6	6	4
1 = Characteristic weakly expressed 7 = Characteristic strongly expressed							
<i>The assessment of the varnish properties was made under standardised printing conditions. In individual cases, under special conditions, as in printing with very thick layers of varnish, the classification of certain properties may be different.</i>							

Don't use oil-based overprint varnishes on food packaging without functional barrier.
Please refer to the individual product literature for more detailed information of the Novacoat® oil-based varnishes.

You are welcome to contact us for further information.

Flint Group
Packaging & Narrow Web
Sieglestrasse 25
70469 Stuttgart, Germany

T +49 711 98 16-0
F +49 711 98 16-700
sheetfed@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH).

Novacoat® oil-based overprint varnishes



Product features	Printing properties						
	Gloss	Matt effect	Wet on Wet suitability	Wet on Dry suitability	Setting	Rub protection	Suitability for Perfecting
ishes – for the production of printed products with European Ecolabels							
High gloss varnish based on BIO-binders that complies with the requirements of the EU Ecolabel, the Austrian UZ24 and the Nordic Ecolabel for printed material.	6	-	7	5	5	7	7
Silk matt varnish based on BIO-binders that complies with the requirements of the EU Ecolabel, the Austrian UZ24 and the Nordic Ecolabel for printed material.	-	3	7	5	5	6	6
Matt varnish based on BIO-binders that complies with the requirements of the EU Ecolabel, the Austrian UZ24 and the Nordic Ecolabel for printed material.	-	6	7	5	5	6	6
1 = Characteristic weakly expressed 7 = Characteristic strongly expressed							
The assessment of the varnish properties was made under standardised printing conditions. In individual cases, under special conditions, as in printing with very thick layers of varnish, the classification of certain properties may be different.							

Don't use oil-based overprint varnishes on food packaging without functional barrier.
Please refer to the individual product literature for more detailed information of the Novacoat® oil-based varnishes.

More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

Flint Group
Packaging & Narrow Web
Sieglestrasse 25
70469 Stuttgart, Germany

T +49 711 98 16-0
F +49 711 98 16-700
sheetfed@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH).